

LED CANOPY LIGHT



LED Canopy Light

- Ideal for indoor or half outdoor lighting, like indoor parking, gas stations, stairwells, passageway's, toll booth's, waiting rooms, etc
- IP65 Waterproof, perfect for any damp or wet Locations.
- Resists rust, corrosion, cracking and any electrical shocks or fires due to moisture
- Corporate & office, education, government, healthcare industrial & warehouse, municipal, parking, petroleum & convenience stores, recreation & public venues, restaurants & hospitality, retail & grocery



Features

- Photocell dusk to dawn
- Reflective lens design to optimize lighting efficiency and minimize glare
- The super thin appearance design conforms to modern aesthetic
- Cast aluminum thermal management for optimal heat sinking
- Suitable for recessed or surface mounted installation
- Protective powder coating for lasting appearance
- PC cover milky & transparent
- Working temperature(F): -30° F to 130°F
- High output 150LM/W SMD3030 chips
- Sturdy die-cast aluminum housing
- IP65 rating for outdoor use
- Instant start, no noise, no flickering
- Mounts to standard junction boxes
- Adjustable CCT: 4500K/ 5000K/ 5700K
- Adjustable power: 60%/ 80%/ 100%
- Top quality with 5 years warranty



CCT Adjustable



Power Adjustable




Applications

Airport, auto dealership, corporate & officem, education, government, healthcare, industrial & warehouse, municipal, parking, petroleum & convenience stores, recreation & public venues, restaurants & hospitalityretail & grocery




Sports Centers



Stations




Workshop




Gas Stations

INSTALLATION INSTRUCTIONS


Ceiling Installation Warning: Turn off the power before installation




1. Unscrew the bracket screws and remove the mounting plate from the lamp housing.



2. Secure the mounting plate to the ceiling using screws.




3. Insert the clip ring of the plate into the latch of the light fixture housing, and hang the fixture on the bracket.
4. Disconnect the power supply and properly connect the fixture's wiring (live wire, neutral wire, and ground wire) to the corresponding power supply wiring.




5. If there are color temperature and power adjustment functions, set them to the desired settings.
6. Push the fixture into the plate and tighten the screws to secure the fixture in place.

Suspension Rod Installation




1. Connect the lamp input line to the mains.



2. Twist the light fixture to the installation pole to secure it.

PACKAGE



Power	Unit	Size	Gross Weight	Volume
40W 60W 80W 100W	1 PC	280x280x95mm / 11.02**11.02**3.74"	2.1 KG / 4.63 lbs	0.007m³
	6 PCS	610x295x295mm / 24.02**11.61**11.61"	13.5 KG / 29.76 lbs	0.053m³