

4"/6"/8"

Round Baffle Can-less Ultra-Slim Recessed Downlight with 5CCT Selector

Project Name:	Order Number:	Prepare by:	Note:	Date:	Type:

BAFFLE CAN-LESS

The **MRSDBA Series** Ultra-Slim LED Downlights are the perfect lighting solution for both residential and commercial. The ultra-slim can-less design allow you to install them in where a recessed can won't fit, no can housing is needed. The quick wiring connectors are coming with the junction box, making the wiring easier-simple place the cable to the connectors to complete the wiring, no wiring nuts and electrical tap needed for the installation. Our downlight provides perfect light performance, showing the true colors of objects and surroundings. You also get all other benefits of LED technology, including longer life to lower maintenance cost, less heat for better energy saving in summer.


Perfect use for residential housings, condominiums, the healthcare facility, shopping centers and hospitality industry.



Select color temperature from

- 2700K **WARM WHITE**
- 3000K **SOFT WHITE**
- 3500K **NATURAL WHITE**
- 4000K **COOL WHITE**
- 5000K **DAYLIGHT**

DIMENSION



MODEL#	LDD3-IN	LDD4-LD	LDD6-IN	LDD8-IN
A	1.25"	1.25"	1.25"	1.25"
B	3.4"	4.7"	6.7"	8.6"

Energy Star® and ETL certified. It can be used to comply with Title-24 and JA8 high efficacy light source requirements.

TECHNICAL SUMMARY

LUMENS	WATTS	EFFICACY	CRI	VOLTAGE	BEAM °	CCT	PF	LIFE	OPERATING TEMP.
650	10W	65 lm/W	90	120V-347V, 60 Hz	95°	2700K/3000K/3500K/4000K/5000K	>0.9	50,000 hrs	-5°F ~ 104°F
900	12W	75 lm/W							
1500	18W	83 lm/W							

PART NUMBER ORDERING SUMMARY

M R S D 6 12W BA - 5CCT - 347V

M	R	S	D	4"/6"/8"	10W/12W/18W	BA	5CCT	347V
	Round	Slim	Downlight	Aper ture	Wattage	Baffle	27K/30K/35K/40K/50K	Voltage

4"/6"/8"**RoundBaffleCan-lessUltra-SlimRecessed Downlight with 5CCT Selector**

Project Name:

Order Number:

Prepare by:

Note:

Date:

CONSTRUCTION

Unit includes spinning metal housing, LED array, heat sink, lens, and foam gasket with baffle white ring.

OPTICS

- High quality PC lens
- Efficiency LED array
- Diffuse for uniform illumination

DRIVER

- High efficiency integral 120V 60Hz constant current dimmable driver.
- Smooth flicker free deep dimming to 10%

MOUNTING

- Pre-installed torsion spring clips
- Can-less design, no can housing needed for the installation
- Junction box included
- Quick wiring, no wiring nuts and electrical tap needed for the installation

LISTING

ETL Listed, Energy Star Listed, Suitable for Wet Locations, Title 24 JA8-2022, RoHS, Air-Tite Certified

WARRANTY

5 years manufacturer warranty, consult factory for more details.
Terms and conditions may apply.

**RECOMMENDED DIMMERS****LUTRON**


- TGCL-153PH-WH
- DVCL-153PR
- P-PKG1W-WH-R
- CTCL-153PDH-WH

LEVITON

- R00-RNL06-TW
- R50-IPL06-10M

COMPATIBLE PRODUCTS (SOLD SEPARATELY)**LDMP-346**

Mounting plate for 3"/4"/6"
can-less downlight

**LDMP-468**

Mounting plate for 4"/6"/8"
can-less downlight

**L3FTCABLE
L10FTCABLE**

3ft/ 10ft Extension cord
for can-less downlight