

4"/6"/8"

Round Baffle Can-less Ultra-Slim Recessed Downlight with 5CCT Selector

Project Name:

Order Number:

Prepare by:

Note:


Date:

Type:

BAFFLE CAN-LESS

The Ultra-Slim LED Downlights are the perfect lighting solution for both residential and commercial. The ultra-slim can-less design allow you to install them in where a recessed can won't fit, no can housing is needed. The quick wiring connectors are coming with the junction box, making the wiring easier-simple place the cable to the connectors to complete the wiring, no wiring nuts and electrical tap needed for the installation. Our downlight provides perfect light performance, showing the true colors of objects and surroundings. You also get all other benefits of LED technology, including longer life to lower maintenance cost, less heat for better energy saving in summer.


Perfect use for residential housings, condominiums, the healthcare facility, shopping centers and hospitality industry.



Select color temperature from

- 2700K WARM WHITE
- 3000K SOFT WHITE
- 3500K NATURAL WHITE
- 4000K COOL WHITE
- 5000K DAYLIGHT

DIMENSION



MODEL#	3-BA	4-BA	6-BA	8-BA
A	1.25"	1.25"	1.25"	1.25"
B	3.4"	4.7"	6.7"	8.6"

TECHNICAL SUMMARY

	LUMENS	WATTS	EFFICACY	CRI	VOLTAGE	BEAM °	CCT	PF	LIFE	OPERATING TEMP.
	650	10W	65 lm/W	90	120V-347V, 60 Hz	95°	2700K/ 3000K/ 3500K/ 4000K/ 5000K	>0.9	50,000 hrs	-5°F ~ 104°F
	900	12W	75 lm/W							
	1500	18W	83 lm/W							

PART NUMBER ORDERING SUMMARY

M R S D 6 12W BA - 5CCT - 347V

M	R Round	S Slim	D Downlight	4"/6"/8" Aper ture	10W/12W/18W Wattage	BA Baffle	5CCT 27K/30K/35K/40K/50K	347V Voltage
---	------------	-----------	----------------	-----------------------	------------------------	--------------	-----------------------------	-----------------

4"/6"/8"**RoundBaffleCan-lessUltra-SlimRecessed Downlight with 5CCT Selector**

Project Name:

Order Number:

Prepare by:

Note:

Date:

Type:

CONSTRUCTION

Unit includes spinning metal housing, LED array, heat sink, lens, and foam gasket with baffle white ring.

OPTICS

- High quality PC lens
- Efficiency LED array
- Diffuse for uniform illumination

DRIVER

- High efficiency integral 120V 60Hz constant current dimmable driver.
- Smooth flicker free deep dimming to 10%

MOUNTING

- Can-less design, no can housing needed for the installation
- Pre-installed torsion spring clips
- Junction box included
- Quick wiring, no wiring nuts and electrical tap needed for the installation

LISTING

ETL Listed, Energy Star Listed, Suitable for Wet Locations, Title 24 JA8-2022, RoHS, Air-Tite Certified

WARRANTY

5 years manufacturer warranty, consult factory for more details.
Terms and conditions may apply.

**JUNCTION BOX INCLUDED****RECOMMENDED DIMMERS****LUTRON**

- TGCL-153PH-WH
- DVCL-153PR
- P-PKG1W-WH-R
- CTCL-153PDH-WH

LEVITON

- R00-RNL06-TW
- R50-IPL06-10M

COMPATIBLE PRODUCTS (SOLD SEPARATELY)

Mounting plate for 3"/4"/6"
can-less downlight



Mounting plate for 4"/6"/8"
can-less downlight



3ft/ 10ft Extension cord
for can-less downlight